

# Taunton Deane Borough Council

## Licensing Committee – 28 August 2013

### Part II - Testing Regime for Hackney Carriages and Private Hire Vehicles

#### Report of the Licensing Officer

(This matter is the responsibility of Executive Councillor Ken Hayward)

#### 1. Executive Summary

Members are asked to consider the Hackney Carriage and Private Hire Vehicle Testing Regime within Taunton Deane and the recommendations set out at section 11 of the report with regard to replacing the current 'Part II test' with a new 'Plate test'.

#### 2. Background

- 2.1 The part II test has remained unchanged since its introduction in 2007. Its purpose is to ensure that any vehicle licensed by the Council is safe, comfortable and visually acceptable. The part II test covers those areas not included within the MOT that all licensed vehicles are also required to obtain. It can only be undertaken by the Council's Nominated Testing Stations.
- 2.2 Information received from the Taxi Trade has shown the current part II test to be unfit for purpose. They have also expressed a will for the testing regime to be improved to ensure vehicles within the Borough meet a high standard. The Council's Nominated Testing Stations have also found the part II test wanting in areas such as vehicle modifications and the ability for vehicle testers to make recommendations.

#### 3. Report

- 3.1 Taking into account advice from the Nominated Testing Stations, the Hackney Carriage and Private Hire National Inspection Standards, shown at **Appendix 1** and through research of vehicles tests used by other Local Authority's, a new set of vehicle testing criteria has been drafted to replace the current criteria as contained within the Council's taxi policy document, the Private Hire and Hackney Carriage Drivers, Vehicles and Operators Handbook.
- 3.2 A list of the current criteria used in conjunction with the part II test is shown at **Appendix 2**. A proposed insertion for the Handbook is shown at **Appendix 3**. The new set of criteria will form part of a rebranding of the part II test. The test will be

renamed the 'plate test' for clarity. The proposed inspection sheet to be used by the testing station inspectors is shown at **Appendix 4**.

- 3.3 One of the notable changes in plate test is the facility for the vehicle inspector to be able to recommend to the licensing authority that a licence should not be issued to the vehicle being tested, on matters other than those contained within the test criteria. This allows the licensing authority to benefit from the expertise of the inspector, who may have concerns over the safety of certain areas of the vehicle which would not be covered by the plate test criteria. We hope that this will ensure the closing of gaps in the current system.
- 3.4 The proposed Handbook insertion and inspection sheet are due to be introduced to the Taxi Trade on Friday 16 August and any feedback received will be considered before the final version is produced.

#### **4. Finance Comments**

- 4.1 With reference to the report by Ian Carter and the recommendations within it, there is a potential for costs to the trade increasing for those operators that wish to have MOTs carried out by testing stations other than those nominated by the Council to carry out the plate test.

#### **5. Legal Comments**

- 5.1 Under the Local Government (Miscellaneous Provisions) Act 1976 Section 48, the Council is required to satisfy itself that any private hire vehicle is (a) in a suitable mechanical condition and (b) safe. Section 48 effectively prohibits the Council from granting a private hire vehicle licence unless it is so satisfied. The legal position in relation to hackney carriages is slightly different, although under Section 47 a licensing authority may impose such licence conditions as it considers reasonably necessary.
- 5.2 In discharging its responsibilities under the 1976 Act, the Council as licensing authority is entitled to implement its own test of compliance in order to satisfy the criteria mentioned above in 5.1.

#### **6. Links to Corporate Aims**

Although there are no direct links to the corporate aims the provision of an effective licensing regime benefits local businesses and the public alike in full accordance with the Council's Corporate Strategy. Reviewing the service allows the Council to continue to demonstrate good governance.

#### **7. Environmental and Community Safety Implications**

- 7.1 None.

## **8. Equalities Impact**

- 8.1 The implementation of the plate test will promote equality in the district of Taunton Deane, by ensuring that Hackney Carriages and Private Hire vehicles licensed by the Council are suitable so as to convey all classes of the public in both safety and comfort.

## **9. Risk Management**

- 9.1 None.

## **10. Partnership Implications (if any)**

- 10.1 Existing partnerships with Nominated Testing Stations will be affected as Service Level Agreements/partnership activities will need to be amended.
- 10.2 Should the Committee approve the plate test, officers will recommend that it be adopted by West Somerset Council licensing authority, in line with the current partnership and to improve standardisation across the two authorities.

## **11. Recommendations**

- 11.1 That Members approve the replacing of the part II test with a new plate test from November 2013.
- 11.2 That Members approve that the approval of any further changes to the plate test be delegated to the Chair of the Licensing Committee and Licensing Manager.

**Contact:** John Rendell  
01823 356343  
j.rendell@tauntondeane.gov.uk

# Hackney Carriage and Private Hire Vehicle

## NATIONAL INSPECTION STANDARDS



A best practice guide produced by the Hackney Carriage and Private Hire Inspection Technical Officer Group

## Foreword

There are numerous bodies inspecting hackney carriage and private hire vehicles, VOSA is supportive of the Public Authority Transport Network (PATN) initiative to develop and share best practice. A common standard applied consistently across the country will no doubt benefit all involved in the industry.

VOSA hopes that local authorities consider the guide when setting inspection standards and actively participate in its future development.

### **Philip Bailey**

SVA and IVA Policy Engineer (Light Vehicles)  
Vehicle & Operator Services Agency  
Roadworthiness & Testing Policy Group



# **BEST PRACTICE GUIDE FOR THE INSPECTION OF HACKNEY CARRIAGE & PRIVATE HIRE VEHICLES**

## **PART 1**

### **INTRODUCTION**

This best practice guide sets out the procedures and standards for those who carry out inspections of hackney carriage & private hire vehicles. It is recommended that the guide is also made freely available to owners, proprietors, operators and drivers of hackney carriage & private hire vehicles, who may find it useful as it details the standards that vehicles are subjected to. The guide also explains the reasons why, a vehicle presented for inspection, has not been issued with a pass certificate.

## INTRODUCTION

### 1.1 BEST PRACTICE GUIDE

This Best Practice Guide has been prepared by the Technical Officer Group (TOG) to assist Hackney Carriage (HC) and Private Hire Vehicle (PHV) operators, vehicle presenters, licensing authorities and vehicle inspectors

It is intended that this Best Practice Guide will endorse a *minimum* national vehicle inspection standard. It will be appreciated that it is for individual local licensing authorities to reach their own decisions, both on overall policies and on individual inspection standards, in the light of their own operational needs and geographical circumstances.

Various interested parties, including the Department for Transport (DfT), Vehicle & Operator Services Agency (VOSA), Disabled Persons Transport Advisory Committee (DPTAC) and the Institute of Licensing, have been consulted on this Best Practice Guide.

The Technical Officer Group commends the *DfT* for the production of the Taxi and Private Hire Vehicle Licensing: Best Practice Guidance. Vehicle operators, local licensing authorities and vehicle inspectors are strongly advised to refer to the *DfT* guide in conjunction with this Best Practice Guide. More information can be obtained on the *DfT* web site at:

[www.dft.gov.uk](http://www.dft.gov.uk)

### 1.2 APPLICATION TO DEVOLVED ADMINISTRATIONS

The Department for Transport (DfT) has responsibility for HC and PHV legislation in England and Wales and, accordingly, the guidance that has been published will be directed at local authorities in England and Wales. Responsibility for HC and PHV licensing in Scotland and Northern Ireland is devolved, but the respective Administrations have been involved in the preparation of the Licensing Guidance and will decide for themselves the extent to which they wish to make use of or adapt to suit their own purposes.

### 1.3 TECHNICAL SAFETY ISSUES

The aim of a local licensing authority is to protect the public. Local licensing authorities will be aware that the public should have reasonable access to safe and well maintained HC and PHVs. For example, it is clearly important that somebody using a HC or PHV should be confident that the vehicle is safe.

To this end, this best practice guide will detail specific vehicle safety issues based on expert technical knowledge and experience of the Technical Officer Group (TOG). This guide will focus therefore on technical safety issues and make recommendations towards safe working practices.

Local licensing authorities will want to ensure that each of their various licensing requirements is properly justified by the risk it aims to address. This is not to propose that a detailed, over-zealous inspection regime creates difficulties for the HC and PHV trades but primarily to promote vehicle safety for the protection of passengers and not for the benefit of operators.

#### **1.4 SCOPE OF THE GUIDANCE**

This guidance deliberately seeks to embrace safety aspects of vehicle inspections using, as a basic inspection standard, those laid down in The MOT Inspection Manual for Car & Light Commercial Vehicle Testing issued by VOSA. This Best Practice Guide provides additional testing requirements to those in the MOT Inspection Manual. It is advised that local licensing authorities use the Best Practice Guide in conjunction with the VOSA MOT Inspection Manual as an advocate to public safety.

This Best Practice Guide has been developed to provide all local licensing authorities with a benchmark with regard to vehicle inspections and safety.

#### **1.5 SPECIFICATION OF VEHICLE TYPES THAT MAY BE LICENSED**

The legislation gives local authorities a wide range of discretion over the types of vehicle that they can license as HC or PHVs. Some authorities specify conditions that in practice can only be met by purpose-built vehicles but the majority license a range of vehicles.

Normally, best practice is for local licensing authorities to adopt the principle of specifying as many different types of vehicles as possible. Indeed, local licensing authorities might usefully specify only general criteria, (such as vehicles with four doors as HC) leaving it open to the HC and PHV trades to put forward vehicles of their own choice which can be shown to meet those criteria. In that way, there can be flexibility for new vehicle types to be readily taken into account.

It is suggested that local licensing authorities should be particularly cautious about specifying only purpose-built HC, with the strict constraint on supply that this implies. (There are at present only two designs of purpose-built HC.) However, purpose-built vehicles are amongst those that a local licensing authority could be expected to license.

#### **1.6 ACCESSIBILITY**

In addition to their general conditions, local licensing authorities will want to consider the accessibility for disabled people (including - but not only - people who need to travel in a wheelchair) of the vehicles they license as Hackney Carriage. For more details, see Section 2 – Accessibility.

Licensing authorities will be aware that it remains the Department for Transport's intention to make accessibility regulations for Hackney Carriage vehicles under the Disability Discrimination Act 1995. In the meantime, licensing authorities are encouraged to introduce HC accessibility policies for their areas.



## 1.7 TYPE APPROVAL

It may be that from time to time a local licensing authority will be asked to license, as a HC or PHV, a vehicle that has been imported independently (that is, by somebody other than the manufacturer). Such a vehicle might meet the local licensing authority's criteria for licensing, but may nonetheless be uncertain about the wider rules for foreign vehicles being used in the UK. Such vehicles will be subject to the 'type approval' rules. For passenger cars up to 10 years old at the time of first GB registration, this means meeting the technical standards of either:

- European Whole Vehicle Type approval;
- British National Type approval; or
- British Single Vehicle Approval (before 29 April 2009) or:
- Individual Vehicle Approval (from 29 April 2009)

Most registration certificates issued since late 1998 should indicate the approval status of the vehicle. Further information about these requirements and the procedures for licensing and registering imported vehicles can be seen at:

[www.dft.gov.uk](http://www.dft.gov.uk)

**It is important for local licensing authorities to insist that at least one of the above 'type approvals' is produced prior to any imported vehicle being licensed as a Hackney Carriage or Private Hire Vehicle.**

### Voluntary Inspections

Vehicles that are already registered for use in the UK are not eligible for a Single Vehicle Approval, however, there are situations where evidence of compliance with the approval standard would be beneficial or be a requirement. An example would be a local licensing authority that may require evidence of compliance for a vehicle that has been modified since original registration, or where evidence of compliance is being used as part of a contractual agreement on a modified vehicle. To facilitate this requirement a non-statutory "Voluntary SVA" or "Voluntary IVA" test is available. The test criteria applied will be dependant on the vehicle category/class nominated on the application form VSVA 1. The fees are the same as those appropriate to the particular class of vehicle/test required other than VAT is payable. If the vehicle is found to meet the requirements a letter of compliance with the technical standards will be issued and not a Minister's Approval certificate. The letter of compliance is not acceptable for First Licensing/Registration purposes.

## 1.8 VEHICLE TESTING

There is considerable variation between local licensing authorities on vehicle testing. This best practice guide provides local licensing authorities with a *minimum* standard for vehicle inspections. All HC and PHV must be maintained to no less than the standards set out in the VOSA publication 'MOT Inspection Manual - Car and Light Commercial', ISBN 0-9549239-0-1.

As the term implies, hackney carriage and private hire vehicles are vehicles used for hire and reward purposes and as such are subject to much higher annual mileages and more arduous driving than normal private vehicles. Therefore, in the interests of passenger and other road user's safety, a more stringent maintenance and testing regime is required.

The purpose of the HC & PHV test is to confirm vehicles meet these more stringent standards. Vehicles must be submitted fully prepared for the test. It is not intended that the test be used in lieu of a regular preventative maintenance programme. If in the opinion of the vehicle examiner the vehicle has not been fully prepared, the test will be terminated and a further full test could be required.

It is an offence under the road traffic regulations to use an unroadworthy vehicle on the public highway.

HC & PHV operators failing to maintain their vehicles in a safe and roadworthy condition may have their licence suspended, curtailed or revoked by the Local Licensing Authority.

This Best Practice Guide should be read in conjunction with Vehicle & Operator Services Agency (VOSA) publication 'MOT Inspection Manual - Car and Light Commercial Vehicle Testing', ISBN 0-9549239-0-1 or as amended. This best practice guide provides a working document for those who inspect, maintain and prepare vehicles for inspection prior to being issued with a hackney carriage or private hire licence. Although detailed in its content the best practice guide is not exhaustive.

However, in assessing the mechanical condition of a vehicle, it is more likely an item which would ordinarily pass an MOT test with an advisory note, could fail the HC & PHV test.

## 2 NOVELTY VEHICLES (STRETCHED LIMOUSINES)

This section of the best practice guide offers advice to local licensing authorities on the requirements for licensing novelty vehicles. The standard of the test for novelty vehicles will be at the same standard as for other private hire vehicles. That is; as a basic inspection standard, those laid down in The MOT Inspection Manual for Car & Light Commercial Vehicle Testing issued by VOSA and this best practice guide. *(For the purpose of clarity, novelty vehicles in this guide will refer to stretch limousines only until such times as further guidance is obtained on any other such vehicle, i.e. fire tenders etc).*

A novelty vehicle shall only be registered as a private hire vehicle if it complies with the following conditions:

- Vehicles with no more than 8 passenger seats as indicated on the V5C. The V5C will state the number of seats and **must be produced to the local licensing authority prior to the vehicle being licenced or inspected**. If the number of seats differs to what is indicated on the V5C, then contact VOSA and your local area Traffic Commissioner immediately. Failure to produce a valid and current V5C for the vehicle to be tested could result in refusal to inspect the vehicle.
- Evidence of either European Community Whole Vehicle Type Approval (ECWVTA) or Single Vehicle Approval (SVA) or Individual Vehicle Approval (IVA) being presented for inspection.
- Local licensing authorities may consider, as novelty vehicles are not factory produced, that a recommended vehicle maintenance inspection be applied every 10 weeks. The frequency of maintenance inspections is recommended by Traffic Commissioners, VOSA and the National Limousine and Chauffeur Association (NLCA).
- The inspection standards to be applied to novelty vehicles are the same standards as those applied to other hackney carriage and private hire vehicles with the following additions:
  - Any additional item previously mentioned in this paragraph with regard to seating capacity, the production of the relevant documents and frequency of vehicle inspections.
  - See Section 4 – Tyres and roadwheels. Reference in this section is made to tyre rating to be applied to novelty vehicles.
  - See Section 12 - Vehicle Identification Number (VIN). VIN markings should be checked to ensure compliance, seating capacities and undue stresses.

Local licensing authorities are strongly advised to obtain a declaration, from the operator of a licensed novelty vehicle, that the vehicles with side facing seats will never be used to carry passengers under 16 years of age, **regardless of whether the vehicle is fitted with or without seatbelts**.

It is strongly advised that notices forbidding children to be carried in side facing seats are displayed in prominent positions, i.e. on entry to the passenger compartment and on either side of the passenger compartment. Local licensing authorities may also require additional outward facing signs adjacent to all entrance/exit doors to the passenger compartment.

### **3 GENERAL INFORMATION**

Only vehicles complying with the following conditions will generally be considered for licensing as private hire vehicles: -

- Cars fitted with at least four doors and four wheels.
- Right-hand drive vehicles - with the exception of stretch limousines (where applicable).
- Vehicles with adequate space for luggage.
- Vehicles must be capable of carrying at least four and not more than eight passengers in addition to the driver.
- With the exception of stretch limousines, vehicles will not be accepted with blacked out windows. Passengers being carried in the vehicle must be visible from the outside. In *exceptional circumstances*, tinted windows may be acceptable.
- To allow a thorough examination of a vehicle or any part thereof, it must be presented for test in a clean condition. The vehicle presented, will fail the test if, in the opinion of the vehicle examiner, the vehicle is so dirty that it would be unreasonable for the test to be carried out.
- A test will not be carried out unless the License fee/Examination Fee has been paid in advance.

#### **Statement of Undertakings and Declaration:**

In the interests of road and passenger safety, the licenced operator undertakes to make proper arrangements so that vehicles are kept in a roadworthy condition at all times.

## ACKNOWLEDGEMENTS

Name	Organisation	Position
Don Allison	Luton BC	Transport Manager
Phil Clifford	St. Edmundsbury BC	Fleet & Technical Manager
Chris Ruane	Freight Transport Association	Sector Head Public Authorities, Waste, Utilities, Construction & Plant
Andy Mair	Freight Transport Association	Head of Engineering Policy
Barry Pearson	Staffordshire County Council	Technical Officer
Simon Smith	Luton BC	Fleet Manager
Derek Rooker	Barnsley MBC	Fleet Engineer
Dave Moyle	Vale of Glamorgan	Workshops Supervisor
Barry Richards	Bath & North East Somerset Council	Service Team Manager – Fleet Management
Kevin Spiers	Oxford City Council	Transport Workshop Coordinator
Ken Stone	Liverpool City Council	Principal Licensing Officer
Dave Colligan	Liverpool City Council	Principal Enforcement Officer
Marten Pleaden	Walsall Council	Vehicle Examiner
Martin Hamer	City of Bradford MDC	Principal Licensing Officer
Paul Dibb	City of Bradford MDC	Workshop Manager
Adam Snape	Worcestershire CC	Fleet Manager
Jamie Robson	Worcestershire CC	
Brendan McNamara	City of Wakefield MDC	Transport Operations Manager
Rod Darton	Chichester DC	Assistant Director Contact Services
John Hoole	Chichester DC	Transport Manager
Dave Pike	Vale of Glamorgan	Workshop Foreman
Keith Miller	Milton Keynes Council	Fleet Manager
Kevin Lewis	Neath & Port Talbot CBC	Fleet Technical Supervisor
Jim Sullivan	Neath & Port Talbot CBC	Licensing Manager
John Webb	Salisbury DC	Licensing Officer
Paul Stretford	Wiltshire CC	Fleet Group
Mike Tonks	Salisbury DC	Transport Manager
Rob Armye	Wiltshire County Council	Fleet Inspector

# **BEST PRACTICE GUIDE FOR THE INSPECTION OF HACKNEY CARRIAGE & PRIVATE HIRE VEHICLES**

## **PART 2**

### **PROCEDURES & STANDARDS OF INSPECTION**

This best practice guide sets out the procedures and standards for those who carry out inspections of hackney carriage & private hire vehicles.

It is recommended that the guide is also made freely available to owners, proprietors, operators and drivers of hackney carriage & private hire vehicles, who may find it useful as it details the standards that vehicles are subjected to. The guide also explains the reasons why, a vehicle presented for inspection, has not been issued with a pass certificate.

## CONTENTS

Section	Subject	Page Number
<b>1</b>	<b>Lighting and signalling equipment:</b>	<b>13</b>
	1.3 Stop Lamps – High Level Stop Lamps	<b>14</b>
	1.8 Electrical Wiring and Equipment	<b>15</b>
	1.9 Additional Lamps	<b>16</b>
<b>2</b>	<b>Steering:</b>	<b>18</b>
	2.1 Steering Control – Steering Wheel	<b>19</b>
	2.1 Steering Control – Steering Column	<b>20</b>
	2.4 Suspension Spring Units & Linkage	<b>21</b>
<b>3</b>	<b>Brakes:</b>	<b>22</b>
	No additional inspection requirements	
<b>4</b>	<b>Tyres &amp; Roadwheels:</b>	<b>23</b>
	4.1 Tyres - Condition	<b>24</b>
<b>5</b>	<b>Seat Belts:</b>	<b>25</b>
	No additional inspection requirements	
<b>6</b>	<b>Body &amp; Structure:</b>	<b>26</b>
	6.1 Vehicle Body and Condition – (Exterior)	<b>27</b>
	6.1 Vehicle Body, Security and Condition – (Interior)	<b>28</b>
	6.2 Doors and Seats	<b>30</b>
	6.5 Bumper Bars	<b>32</b>
<b>7</b>	<b>Fuel &amp; Emissions:</b>	<b>33</b>
	7.1 Exhaust System	<b>34</b>
	7.2 Fuel System – Pipes & Tanks	<b>35</b>

<b>8</b>	<b>Drivers View of the Road:</b>	<b>36</b>
	8.1 Mirrors	<b>37</b>
	8.3 Windscreen – View top the Front	<b>38</b>
	8.5 Window Glass or Other Transparent Material	<b>39</b>
<b>9</b>	<b>Tricycles &amp; Quadricycles</b> No additional inspection requirements	<b>40</b>
<b>10</b>	<b>Additional Requirements:</b>	<b>41</b>
	10.1 Speedometer	<b>42</b>
	10.2 Transmission	<b>43</b>
	10.3 Engine & Transmission Mountings	<b>45</b>
	10.4 Oil & Water Leaks	<b>46</b>
	10.5 Luggage/Load Space	<b>47</b>
10.6 Trailers & Towbars	<b>48</b>	
<b>11</b>	<b>Ancillary Equipment:</b>	<b>49</b>
	11.1 Wheelchair Restraint & Access Equipment	<b>50</b>
	11.2 Fire Extinguisher	<b>52</b>
	11.3 First Aid Kit	<b>53</b>
<b>12</b>	<b>Novelty Vehicles:</b>	<b>54</b>
	12.1 Vehicle Identification Number (VIN)	<b>55</b>
	12.2 Seating Capacity	<b>56</b>
	12.3 Undue Stresses	<b>57</b>
	12.4 Passenger Notices	<b>58</b>
<b>APPENDIX 'A'</b>	<b>Hackney Carriage &amp; Private Hire - Trailer Inspection Sheet</b>	<b>59</b>
<b>APPENDIX 'B'</b>	<b>Definition of Motor Vehicles</b>	<b>60</b>



# SECTION 1 - LIGHTING AND SIGNALLING EQUIPMENT

## Section Contents:

<b>Sub-section</b>	<b>Subject</b>
1.3	Stop Lamps – High Level Stop Lamps
1.8	Electrical Wiring and Equipment
1.9	Additional Lamps <ul style="list-style-type: none"><li>• Reversing Lamps</li><li>• Front Fog/Driving Lamps</li><li>• For Hire and Roof Signs</li></ul>

### 1.3. STOP LAMPS - HIGH LEVEL STOP LAMPS

<b>Method of Inspection</b>	<b>Reason for Rejection</b>
<p>Any additional stop lamps fitted and connected must be tested. Where high level stop lamps are fitted and there is doubt as to whether they are connected, the benefit of this doubt should be given to the presenter.</p> <p>Check the high level stop lamp where fitted:</p> <ul style="list-style-type: none"><li>a. Is not obscured, and is not obviously incorrectly positioned.</li><li>b. At least 50% of the lamp must be visible from the rear.</li></ul>	<p>High level stop lamp</p> <ul style="list-style-type: none"><li>a. Obscured or obviously incorrectly positioned.</li><li>b. Less than 50% of the lamp not working or obscured</li></ul>

## 1.8. ELECTRICAL WIRING AND EQUIPMENT

<b>Method of Inspection</b>	<b>Reason for Rejection</b>
<p>This examination is limited to that part of the electrical system that can be readily seen without dismantling any part of the vehicle.</p> <p>a. Check all electrical wiring for:</p> <ul style="list-style-type: none"><li>○ Condition</li><li>○ Security</li><li>○ Position</li> <li>○ Signs of overheating</li><li>○ Heavy oil contamination</li></ul> <p>b. Battery and carrier for:</p> <ul style="list-style-type: none"><li>○ Security</li><li>○ Battery for leaks</li></ul> <p>c. Check all switches controlling all obligatory lights</p>	<p>a. Wiring</p> <ul style="list-style-type: none"><li>○ Not adequately insulated</li><li>○ Not adequately secured</li><li>○ Positioned so that it is chafing or clipped to a fuel line or likely to be damaged by heat so that insulation will become ineffective</li><li>○ With clear evidence of overheating</li><li>○ Heavily contaminated with oil</li></ul> <p>b. Battery and carrier:</p> <ul style="list-style-type: none"><li>○ A battery and /or carrier not secure and likely to become displaced</li><li>○ Battery leaking</li></ul> <p>c. Insecurity or malfunction of a switch controlling an obligatory light</p>

## 1.9. ADDITIONAL LAMPS

Method of Inspection	Reason for Rejection
<p>With the ignition switched on check:</p> <p>Reversing lamps</p> <ul style="list-style-type: none"> <li>a. The reversing lamps emit a diffused white light when reverse gear is selected.</li> <li>b. The lamps extinguish when neutral gear is selected</li> <li>c. The lamps are in good working order and are secure.</li> <li>d. The lamps do not flicker when lightly tapped by hand.</li> </ul> <p>Front Fog/Driving Lamps Check that:</p> <ul style="list-style-type: none"> <li>e. A single front fog lamp emitting a white or yellow diffused light illuminates only when dipped beam is selected</li> <li>f. A pair of matched fog lamps both emitting a white or yellow diffused light should illuminate together</li> <li>g. A pair of matched, long-range driving lamps, both emitting a white diffused light should illuminate together.</li> </ul>	<p>A reversing lamp:</p> <ul style="list-style-type: none"> <li>a. That fails to operate or does not emit a white diffused light</li> <li>b. Fails to extinguish when neutral or forward gear is selected</li> <li>c. Are not in good working order or insecure.</li> <li>d. Lamps flicker when tapped lightly by hand.</li> </ul> <p>Front Fog/Driving Lamps</p> <ul style="list-style-type: none"> <li>e. Lamp inoperative or operates other than in dipped beam mode</li> <li>f. Lamps operate incorrectly</li> <li>g. Lamps operate incorrectly</li> </ul>

<b>Additional Lamps (continued)</b>	<b>Reason for Rejection</b>
<p data-bbox="191 305 499 342"><b>Method of Inspection</b></p> <p data-bbox="191 375 533 412">'For Hire' and Roof Signs</p> <p data-bbox="191 444 352 482">Check that:</p> <ul style="list-style-type: none"> <li data-bbox="191 514 722 552">a. Correct style and type of sign fitted.</li> <li data-bbox="191 579 915 617">b. Ensure the sign is securely fastened to the vehicle</li> <li data-bbox="191 617 758 654">c. Check condition and security of wiring</li> <li data-bbox="191 654 762 691">d. Functional test of signs for illumination</li> </ul>	<p data-bbox="1115 305 1423 342"><b>Reason for Rejection</b></p> <p data-bbox="1115 412 1457 449">'For Hire' and Roof Signs</p> <ul style="list-style-type: none"> <li data-bbox="1115 547 2026 612">a. Incorrect colour or details shown on sign, i.e. registration number, vehicle number etc.</li> <li data-bbox="1115 612 1346 649">b. Insecure sign</li> <li data-bbox="1115 649 1860 686">c. Wiring is not in good condition and is loose or chaffed</li> <li data-bbox="1115 686 2026 751">d. Illumination not consistent across the sign, i.e. all light bulb(s) LED(s) illuminated when switched on.</li> </ul>

## SECTION 2 - STEERING

### Section Contents:

<b>Sub-section</b>	<b>Subject</b>
2.1	Steering Control – Steering Wheel
2.1	Steering Control – Steering Column
2.4	Suspension Spring Units and Linkages

## 2.1 STEERING CONTROL - STEERING WHEEL

Method of Inspection	Reason for Rejection
<p>With both hands rock the steering wheel from side to side at right angles to steering column and apply slight downward and upward pressure to the steering wheel rim (in line with column). Note:</p> <ul style="list-style-type: none"><li>a. Fractures in steering wheel hub.</li><li>b. Fractures in steering wheel rim.</li><li>c. Steering wheel spokes loose or fractured.</li><li>d. Jagged edges on steering wheel rim.</li><li>e. If possible, check the retaining device on steering wheel is fitted.</li></ul>	<ul style="list-style-type: none"><li>a. Steering wheel hub fractured.</li><li>b. Steering wheel rim fractured.</li><li>c. A steering wheel spoke loose or fractured.</li><li>d. Jagged edges on steering wheel rim likely to injure the driver.</li><li>e. A steering wheel hub-retaining device not fitted.</li></ul>

## 2.1 STEERING CONTROL - STEERING COLUMN

Method of Inspection	Reason for Rejection
<p>a. Try to lift the steering in line with the steering column and note the movement at centre of steering wheel.</p> <p>b. Push steering wheel away and then pull it towards you. Note any side play.</p> <p>c. While steering wheel is rotated, check for deterioration in any flexible coupling or universal joint of steering column.</p> <p>d. Where practical, check any clamp bolts for presence and security of locking devices. (These may be located in the engine compartment or under chassis).</p>	<p>a. Excessive movement of centre of steering wheel in line with steering column (end float).</p> <p><b>Note:</b> Certain types of steering column might show some movement not due to excessive wear, e.g. those fitted with universal joints or flexible couplings</p> <p>b. Excessive side play indicating worn top bearings or insecure top mounting bracket.</p> <p>c. A flexible coupling or universal joint deteriorated, worn or insecure.</p> <p>d. A coupling clamp bolt or locking device loose or missing.</p>



## 2.4 SUSPENSION SPRING UNITS AND LINKAGES

Method of Inspection	Reason for Rejection
<b>Coil Springs</b> a. Welding repairs	a. Repaired by welding

## **SECTION 3 - BRAKES**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
--------------------	----------------

No additional inspection requirements

## **SECTION 4 – TYRES & ROADWHEELS**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
4.1	Tyres – Condition

## 4.1 TYRES

Method of Inspection	Reason for Rejection
<p><b>Condition of Tyres</b></p> <p>On all the tyres, including spare wheel - <b>where fitted</b>, examine each tyre meets all the requirements laid down in the MOT Inspection Manual for Car &amp; Light Commercial Vehicles (ISBN <b>0-9549239-0-1</b>)</p> <p><b>Note 1</b> Where a doughnut tank is fitted in the boot for LPG, the spare wheel if still carried in the boot must be properly secured. Alternatively, a spare wheel cage installed to manufacturers and British Standards may be fitted to the underside of the vehicle.</p>	<p>In accordance with the MOT Inspection Manual for Car &amp; Light Commercial Vehicles (ISBN <b>0-9549239-0-1</b>)</p> <p><b>Note 2</b> Space saver tyres should only be approved with the support of a method statement highlighting driver responsibilities with regard to the maximum permitted speed and that space savers are a temporary 'get-you-home tyre'.</p>
<p><b>SPECIAL NOTICE – STRETCHED LIMOUSINES:</b> In the case of American imported stretched limousines, vehicle inspectors will need to be vigilant when inspecting tyres for suitability. Most converted stretched limousines are converted from Ford Lincoln Town Cars with a number of Cadillac variants also. In approved 'stretch' limousine conversions, the maximum weight is approximately 7,100lbs (3.2tonnes) and care should be exercised when determining suitable tyre ratings. Generally speaking a Ford Lincoln or Cadillac would require a tyre rating index of at least 107 T, which gives a load rating of 2,149 lbs (975 kgs) with a maximum speed of 118 miles per hour.</p>	<p><b>STRETCHED LIMOUSINES</b> More information, guidance and the procurement of suitable tyres can be obtained from: North Hants Tyres &amp; Wheels, Henry John House 2 Ivy Road, Aldershot GU12 4TX Telephone: 01252 318666</p> <p style="text-align: center;"><b>OR</b></p> <p>National Limousine &amp; Chauffeur Association on: <a href="http://www.nlca.co.uk">www.nlca.co.uk</a></p>

## **SECTION 5 – SEAT BELTS**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
--------------------	----------------

	No additional inspection requirements
--	---------------------------------------

## **SECTION 6 – BODY AND STRUCTURE**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
6.1	Vehicle Body and Condition – (Exterior)
6.1	Vehicle Body, Security and Condition – (Interior)
6.2	Doors and Seats
6.4	Bumper Bars

## 6.1 VEHICLE BODY AND CONDITION – (EXTERIOR)

Method of Inspection	Reason For Rejection
<p><b>Body Condition (Exterior)</b> Examine the body thoroughly for security, corrosion, damage, poor repair/paint match or sharp edges that are likely to cause injury.</p>	<p><b>Body Condition (Exterior)</b></p> <ol style="list-style-type: none"> <li>a. An insecure or missing body panel, trim, step or accessory.</li> <li>b. Any sharp edge whatsoever which may cause injury.</li> <li>c. Heavy scuffing, abrasions or deformation to front and rear bumper.</li> <li>d. More than 8 stone chips visible on a bonnet/grill that has not penetrated to the metal or more than 4 stone chips that have penetrated to the metal.</li> <li>e. More than 8 stone chips on any panel including door edges, provided the base coat has not been penetrated.</li> <li>f. More than 4 stone chips on any panel where the base coat has been penetrated to the metal and is untreated.</li> <li>g. A single dent of more than 80mm, or more than 3 dents of not more than 20mm in any one panel</li> <li>h. More than 4 scratches and or abrasions of more than 50mm in length in any one panel provided that the base coat has not been penetrated.</li> <li>i. Dull, faded paintwork which has lost its gloss finish or paint miss match to a panel(s) to such an extent that it detracts from the overall appearance of the vehicle.</li> <li>j. Evidence of poor repairs and or paint finish to a repaired panel(s) including runs and overspray to adjoining panels/trim that detracts from the overall appearance of the vehicle.</li> <li>k. Obvious signs of rust/corrosion of any size particularly those that are covered by advertising signs.</li> <li>l. Lack of clearly displayed or omission of 'No Smoking' signs.</li> </ol>

**6.1 VEHICLE BODY, SECURITY AND CONDITION – (INTERIOR)**

<b>Method of Inspection</b>	<b>Reasons For Rejection</b>
<p><b>Body Condition (Interior)</b></p> <ul style="list-style-type: none"> <li>a. Examine thoroughly the interior for damaged, insecure or loose fixtures, fittings or accessories.</li> <li>b. Dirty, missing and worn trim, carpets, seat belts, mats, headlining, boot area and inclusion of prescribed items. Remove mats to inspect carpets underneath for cleanliness and wear.</li> <li>c. Examine interior lights, motion door locks and warning lights.</li> <li>d. Examine heating, demisting and air condition systems for correct operation, including passenger compartment controls where fitted(includes electric front and rear screen demisters)</li> <li>e. Examine all windows ensuring they allow lowering and rising easily.</li> <li>f. Examine interior door locks, grab handles/rails safety covers</li> <li>g. Examine grills/partitions for security and condition</li> <li>h. Examine electrical wiring for condition, security, including intercom systems.</li> </ul>	<ul style="list-style-type: none"> <li>a. Insecure and loose fixtures, fittings or accessories.</li> <li>b. Missing, dirty, soiled, stained worn or insecure trim, carpets, headlining, and mats.</li> <li>c. An inoperative interior light (all lights must illuminate if they are part of the manufacturer’s standard equipment). Missing or defective motion switch/lock or warning lamp not illuminated</li> <li>d. A system(s), which does not function correctly, or any part is missing including vents, controls and switches.</li> <li>e. An opening window that is inoperative or difficult to open and or close mechanism broken/missing.</li> <li>f. Missing, defective or loose door locks, child locks, protective covers grab handles and rails. Grab handles/rails, which are rigid to aid the blind and partially sighted, and are worn to excess.</li> <li>g. A grill/partition which is insecure or has sharp edge which may cause injury to passengers or driver.</li> <li>h. Frayed, chaffing wiring, non-shielded terminals and cables so routed that they cause a trip hazard, cables that can be easily disconnected. Intercom system defective, warning light inoperative and signs illegible/missing.</li> </ul>



Method of Inspection	Reason for Rejection
<p><b>Body Condition (Interior) (continued)</b></p> <p>i. Examine the boot for access, contents, cleanliness, and water ingress.</p> <p>Additional items to be inspected in limousines and novelty vehicles:</p> <p>j. All fixtures and fittings i.e. mirror balls, drinks cabinets, televisions etc must be stored securely and not hinder the ingress or egress from the passenger compartment.</p> <p>k. A notice identifying the maximum seating capacity to be displayed in the passenger compartment and clearly visible to all passengers. It may be necessary to display more than one sign indicating the maximum seating capacity.</p> <p><b>Note: <u>Any vehicle presented in a dirty, untidy condition will not be tested</u></b></p>	<p>i. Unable to open, close and or lock boot lid, failure of boot lid support mechanism, defective seals/evidence of water ingress, dirty boot and or carpets, loose items stored in boot (i.e. spare wheel tools and equipment etc).</p> <p>j. Any fixture or fitting, that is loose or insecure or where walkways are blocked that prevents ease of ingress or egress from the passenger compartment.</p> <p>k. No maximum seating capacity sign or signs displayed. A sign or signs not clearly visible to all passengers</p>

## 6.2 DOORS and SEATS

Method of Inspection	Reason for Rejection
<p><b>Doors and Emergency Exits</b></p> <p>Examine the condition of all doors and emergency exits. Check door locks, striker plates, handles and hinges for security, wear and missing and damaged trim/cover plates.</p> <p>Check markings describing the presence and method of opening emergency exit(s) are readily visible on or adjacent to the exit and are legible.</p> <p>Check that seats are secure, clean and not unduly worn.</p> <p><b>IMPORTANT NOTE: With the exception of ‘novelty vehicles’ only vehicles with forward and rear facing seats will be accepted.</b></p> <p><b>For more information on seating for novelty vehicles see Section 12.2</b></p>	<p><b>Doors and Emergency Exits</b></p> <ol style="list-style-type: none"> <li>a. A door or emergency exit does not latch securely in the closed position.</li> <li>b. A door or emergency exit cannot be opened from both the inside and outside the vehicle from the relevant control in each case.</li> <li>c. Missing, loose or worn handles, lock or striker plate.</li> <li>d. Markings describing the presence and method of opening an emergency exit missing, illegible or incorrect.</li> <li>e. Missing, loose or damaged trim/cover plate.</li> <li>f. Seat cushion(s) stained, torn, holed, worn or insecure. A seat that does not provide adequate support at base or backrest. Torn, slashed or badly stained seats are not acceptable.</li> </ol>

**6.2 DOORS and SEATS** (continued)

<b>Method of Inspection</b>	<b>Reason for Rejection</b>
<p><b>Accessibility: Wheelchair Vehicles</b></p> <p>Door Configurations for wheelchair accessible vehicles:</p> <ul style="list-style-type: none"><li>a. Single rear door – must open to a minimum of 90 degrees and be capable of locking in place.</li><li>b. Twin rear doors – both must open to a minimum of 180 degrees and be capable of being locked in place. This is to enable an attendant (driver or guide) to assist the wheelchair passenger if required.</li></ul>	<ul style="list-style-type: none"><li>a. Door does not open to a full 90 degrees and cannot be secured in the open position</li><li>b. Twin doors do not open to a full 180 degrees and cannot be secured in the open position</li></ul>

## 6.4 BUMPER BARS

<b>Method of Inspection</b>	<b>Reason for Rejection</b>
<p>Examine the bumper bars and check:</p> <ul style="list-style-type: none"><li>a. They are secure to their mountings.</li><li>b. The mountings are secure to the vehicle.</li> <li>c. There is no evidence of damage.</li></ul>	<ul style="list-style-type: none"><li>a. A loose bumper bar or mounting. A weakened bumper bar and/or mounting is insecure because of poor repairs.</li><li>b. A fractured mounting bracket. Mounting bolts so worn or elongated that the bumper bar is likely to detach partially or completely from the vehicle when in use. A bumper bar secured by wire or other temporary means is regarded as insecure and must be rejected.</li><li>c. Bumper bars which have jagged edges, cracks, splits or projections, which may cause injury to persons near the vehicle. Paint miss match or fading which is significantly different to that of the rest of the paintwork.</li></ul>

## **SECTION 7 – FUEL & EMISSIONS**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
7.1	Exhaust System
7.2	Fuel System – Pipes & Tanks

## 7.1 EXHAUST SYSTEM

<b>Method of Inspection</b>	<b>Reason for Rejection</b>
Where applicable, check for presence, security and adequacy of grease shields to hot exhausts.	A heat shield missing, insecure or inadequate

## 7.2 FUEL SYSTEM - PIPES & TANKS

Method of Inspection	Reason for Rejection
<p>a. Examine fuel tank(s) for security and leaks</p> <p>b. Check that fuel tank filler caps are:</p> <ul style="list-style-type: none"><li>○ Present</li><li>○ Of the correct type</li><li>○ Secure and seated properly to ensure correct function of sealing</li></ul> <p>c. Examine pipes to see they are securely clipped to prevent damage by chafing and cracking, and are not in a position where they will be fouled by moving parts</p> <p>d. Check that no fuel pipe runs immediately adjacent to or in direct contact with electrical wiring or the exhaust system</p>	<p>a. Fuel tank insecure or leaking</p> <p>b. A filler cap missing or unsuitable or in such condition that it would not prevent fuel leaking or spilling</p> <p><b>Note:</b> Temporary/emergency fuel caps are not permitted.</p> <p>c. Damaged, chafed, insecure pipes, or pipes so positioned that there is a danger of them fouling moving parts</p> <p>d. A fuel pipe immediately to or in direct contact with electrical wiring or exhaust system</p>

## **SECTION 8 – DRIVERS VIEW OF THE ROAD**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
8.1	Mirrors
8.3	Windscreen – View to the Front
8.5	Window Glass or Other Transparent Material



## 8.1 MIRRORS

Method of Inspection	Reason for Rejection
<p>The number and position of all obligatory mirrors must be checked:</p> <p>a. Check the condition of each mirror reflecting surface and whether a person sitting in the drivers seat can see clearly to the rear</p>	<p><b>Note: A defective additional external mirror is not a reason for rejection.</b></p> <p>a. Mirror condition</p> <ul style="list-style-type: none"><li>• A mirror reflecting surface deteriorated or broken.</li><li>• In such a position that a person sitting in the driver's seat cannot see clearly to the rear.</li></ul>

### 8.3 WINDSCREEN - VIEW TO THE FRONT

Method of Inspection	Reason for Rejection
<p>Sit in the driver's seat and check that there is reasonable view of the road ahead, bearing in mind the original design of the vehicle.</p> <p>a. For all air operated wipers examine:</p> <ul style="list-style-type: none"><li>○ The condition of any visible piping</li><li>○ The function of the operating mechanism, and</li><li>○ The function of necessary valves to protect the braking system</li></ul> <p><b>Note:</b> Equipment or objects not originally fitted to the vehicle as part of the original design must not obstruct the designed forward view of the driver. In particular, objects such as (but not limited to) pennants, cab decorations and external stone guards/visors should not interrupt the view through the swept area by the windscreen wipers.</p>	<p>The position or size of any object restricts the driver's view of the road ahead, bearing in mind the original design of the vehicle.</p> <p>a. Air operated wipers</p> <ul style="list-style-type: none"><li>○ Pipes inadequately clipped or supported</li><li>○ Incorrect function of the wipers or leaking components</li><li>○ Incorrect operation of protection valves</li></ul>

## 8.5 WINDOW GLASS OR OTHER TRANSPARENT MATERIAL

Method of Inspection	Reason for Rejection
<p>a Visually check the condition of all windscreens, internal screens, partitions, side, rear, roof and door windows for cracks, surface damage and discolouration.</p> <p>b Check presence and security of all windscreens, side, roof, or rear windows, or internal screens or partitions.</p> <p>c Check for evidence of obvious leaks from all windscreens and side, rear, roof or door windows.</p> <p>d Check for presence, security and condition of guard rails or barriers at windows, internal screens or partitions</p> <p>e For all vehicles first used before 1 January 1959. As far as is practicable, check that glass fitted to windscreens and outside windows facing to the front is safety glass, except glass fitted to the upper deck of a double deck bus.</p> <p>f For all vehicles used on or after 1 January 1959, as far as is practicable, check that glass used for windscreens and all outside windows is safety glass, or safety glazing.</p> <p>g Vehicles first used on or after 1 June 1978, check that windscreens and other windows, wholly or partly, on either side of the drivers' seat are made from safety glass displaying an acceptable safety mark.</p>	<p>a A crack, surface damage or discoloration in glass or other transparent material that:</p> <ul style="list-style-type: none"> <li>o Impairs the driver's front, side, or rear view of the road, or;</li> <li>o Presents a danger to any person in the vehicle.</li> </ul> <p>b A windscreen or any other outside window missing, or any windscreen, window, internal screen or partition insecure.</p> <p>c Any external window or windscreen is obviously leaking.</p> <p>d A guard-rail or barrier at a window, internal screen or partition missing, insecure or damaged.</p> <p>e The windscreen and/or any outside window facing to the front of a vehicle obviously not safety glass fitted to a vehicle first used before 1 January 1959.</p> <p>f Glass used for a windscreen or an outside window is obviously not safety glass.</p> <p>g For vehicles first used on or after 1 June 1978, that windscreens and/or other windows wholly or partly on either side of the drivers seat that are not made from safety glass display an acceptable safety mark.</p>
<p><b>Note:</b> Marking is not required for safety glass used on vehicles first used before 1 June 1978.</p>	

## **SECTION 9 – Tricycles & Quadricycles**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
--------------------	----------------

	No additional inspection requirements
--	---------------------------------------

## **SECTION 10 – ADDITIONAL REQUIREMENTS**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
10.1	Speedometer
10.2	Transmission
10.3	Engine & Transmission Mountings
10.4	Oil & Water Leaks
10.5	Luggage/Load Space
10.6	Trailers & Towbars

## 10.1 SPEEDOMETER

Method of Inspection	Reason for Rejection
<ul style="list-style-type: none"><li>a. Check that a speedometer is fitted.</li><li>b. Check the condition of the speedometer.</li><li>c. Check that the speedometer can be illuminated.</li></ul>	<ul style="list-style-type: none"><li>a. Speedometer not fitted.</li><li>b. Speedometer not complete or clearly inoperative, or dial glass broken or missing.</li><li>c. The speedometer cannot be illuminated.</li></ul>

## 10.2 TRANSMISSION

Method of Inspection	Reason for Rejection
<p>Examine transmission, check for:</p> <ul style="list-style-type: none"><li>a. Missing or loose flange bolts</li><li>b. Cracked or insecure flanges</li><li>c. Wear in shaft and/or wheel bearings</li><li>d. Security of bearing housings</li><li>e. Cracks or fractures in bearing housings</li><li>f. Wear in universal joints</li><li>g. Deterioration of flexible couplings</li><li>h. Distorted, damaged shafts</li><li>i. Deterioration of bearing housing flexible mountings</li><li>j. Clearance between transmission shafts and adjacent components</li></ul>	<ul style="list-style-type: none"><li>a. A loose or missing flange bolt(s)</li><li>b. A flange cracked, or loose on the transmission shaft</li><li>c. Excessive wear in shaft bearing</li><li>d. A bearing housing insecure to its fixing</li><li>e. A cracked or fractured bearing housing</li><li>f. Excessive wear in a universal joint</li><li>g. Deterioration of a transmission shaft flexible coupling</li><li>h. A damaged, cracked or bent shaft</li><li>i. Deterioration of a flexible mounting of a bearing housing</li><li>j. Evidence of fouling between any transmission shaft and an adjacent component</li></ul>

**10.2 TRANSMISSION (cont'd)**

Method of Inspection	Reason for Rejection
<p>Front Wheel Drive</p> <p>a. Check the drive shaft inner and outer universal joint couplings and constant velocity joints for:</p> <ul style="list-style-type: none"> <li>○ Wear and security</li> <li>○ Damage to flexible rubber or fabric universal joints</li> <li>○ Security and oil contamination of flexible rubber or fabric universal joints</li> <li>○ Condition, presence and security of constant velocity joint gaiters</li> </ul>	<ul style="list-style-type: none"> <li>○ Drive shaft constant velocity or universal joint coupling worn or insecure</li> <li>○ A flexible rubber or fabric universal coupling unit damaged by severe cracking or breaking up</li> <li>○ A flexible rubber or fabric universal coupling unit excessively softened by oil contamination or insecure</li> <li>○ A drive shaft constant velocity joint gaiter split, missing or insecurely mounted</li> </ul>



### 10.3 ENGINE AND TRANSMISSION MOUNTINGS

Method of Inspection	Reason for Rejection
<p>a. Examine condition of:</p> <ul style="list-style-type: none"> <li>○ mountings</li> <li>○ sub-frames</li> </ul> <p>And</p> <p>b. The security to chassis and check for:</p> <ul style="list-style-type: none"> <li>○ fractures</li> <li>○ looseness</li> <li>○ Deterioration</li> </ul>	<p>}          }          }          }          }          }          }          }          }          }          }          }          }</p> <p>Any mounting or sub-frame</p> <ul style="list-style-type: none"> <li>- loose</li> <li>- fractured</li> <li>- deteriorated</li> <li>- inappropriate repair</li> </ul>

## 10.4 OIL AND WATER LEAKS

Method of Inspection	Reason for Rejection
<p>a. Check vehicle for oil and water leaks from any assembly or component to the ground.</p> <p>b. And/or which could be deposited on surrounding bodywork or onto the exhaust system.</p>	<p>a. An oil or water leak, from any assembly, which deposits fluids underneath the vehicle whilst stationary.</p> <p>b. Leaks which, when the vehicle is moving, could be deposited upon the surrounding bodywork, exhaust and brake system so that it would:</p> <ul style="list-style-type: none"><li>○ Contaminate areas</li><li>○ Could potentially cause a health, safety or fire risk</li></ul>
<p><b>Note:</b> If necessary, the engine can be run at <u>idle speed</u> to confirm the existence of an oil leak.</p>	

## 10.5 LUGGAGE/LOAD SPACE

<b>Method of Inspection</b>	<b>Reason for Rejection</b>
<p>Physical separation is not so much an issue as is the safety of passengers in the event of an accident. The luggage should therefore be secure and prevented from becoming dislodged in an accident in such a manner as may cause injury. Such security can be by means of a sheet or net, which could be anchored to the floor of the luggage area. Clearly if the luggage compartment is not physically separated from the passenger compartment then care will need to be taken so as not to carry any hazardous items such as fuel cans, detergents or other loose items that could leak if they become damaged.</p>	<ul style="list-style-type: none"><li>○ Load restraint system, if required, not present at time of test.</li><li>○ Load restraint system faulty or unserviceable.</li></ul>

## 10.6 TRAILERS & TOWBARS

Method of Inspection	Reason for Rejection
<p><b>TRAILERS</b></p> <p>a. Where a local licensing authority permits the use of trailers for the carriage of luggage, then the trailer needs to be presented for test along with the vehicle that will be authorised to tow it. The trailer will also need to display the appropriate registration plate and a licence plate.</p> <p><b>Note:</b></p> <p>Trailers presented for inspection should be built by an approved or recognised trailer manufacturer.</p> <p>An example of a typical trailer inspection sheet can be found at Appendix 'A'.</p> <p><b>TOW-BARS</b></p> <p>b. Where tow bars are fitted checks must be made on the condition and security to the towing vehicle.</p>	<p>a. Rejections as indicated on the trailer inspection sheet shown at Appendix 'A'</p> <p>b. Rejections as indicated on the trailer inspection sheet shown at Appendix 'A'</p>

## **SECTION 11 – ANCILLARY EQUIPMENT**


### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
11.1	Wheelchair Restraint & Access Equipment
11.2	Fire Extinguisher
11.3	First Aid Kit

## 11.1 WHEELCHAIR RESTRAINT & ACCESS EQUIPMENT

Method of Inspection	Reason For Rejection
<p><b>WHEELCHAIR RESTRAINT</b></p> <p>a. Where applicable check condition and operation of wheelchair restraint.</p> <p>b. A system for the effective anchoring of wheelchairs shall be provided within the vehicle in all spaces designated as wheelchair spaces.</p> <p><b>WHEELCHAIR ACCESS &amp; EQUIPMENT</b></p> <p>A vehicle shall be fitted with either of the following forms of wheelchair access equipment:</p> <p><u>Ramps</u></p> <p>c. Check that appropriate ramps fitted are securely installed in the designated storage area. Examine for damage, deformity, sharp edges etc. and provision of anti-slip covering.</p> <p><u>Wheelchair lift</u></p> <p>d. A purpose designed wheelchair lift shall conform to the LOLER 98 Regulations. A report, confirming that the lifting equipment is safe to use, shall be presented at the time of the vehicle inspection. Vehicles presented for inspection with a wheel chair lift will require a LOLER certificate that is valid for a period of six months from the date of issue.</p> <p><b>Note:</b></p> <p>Passenger lifting equipment will need to be thoroughly examined by a competent person, in use, at least once every six months.</p>	<p>a. A wheelchair restraint is defective, worn or missing.</p> <p>b. Wheelchair anchorage systems and devices does not conform to European Directive 76/115 EEC (as amended by 90/629 EEC). See Appendix 'B'.</p> <p>c. Ramps missing, insecurely stored, damaged/deformed, anti-slip covering in poor condition or missing.</p> <p>d. Vehicle not presented with a valid or current LOLER certificate.</p>

## 11.1 WHEELCHAIR RESTRAINT & ACCESS EQUIPMENT (Continued)

Method of Inspection	Reason for Rejection
<p>e. Any purpose designed wheelchair access ramp that is carried must be lightweight and easy to deploy. The installed ramp shall have visible reference to safe working load of 250 kgs and certified to BS 6109.</p> <p>f. Wheelchair access equipment shall be fitted either into the rear or side access door of the vehicle. Where it is fitted to a side door this shall be the door situated on the near side of the vehicle, i.e. kerbside when stopped in a normal road.</p> <p>g. The aperture of the door into which the access equipment is fitted shall have minimum clear headroom in its central third of 48 inches (1,220mm). The measurement shall be taken from the upper centre of the aperture to a point directly below on either, the upper face of the fully raised lift platform, or the upper face of the ramp fully deployed on level ground.</p> <p>h. A locking mechanism shall be fitted that holds the access door in the open position whilst in use.</p> <p>i. All wheelchair tracking must be fit for purpose and structurally sound.</p>	<p>e. The installed ramp does not have any visible reference to a maximum safe working load or certification to BS 6109.</p> <p>f. Wheelchair access equipment is fitted to the off- side access door of the vehicle.</p> <p>g. There is not clear headroom in the aperture within the central third of 48 inches (1,220mm).</p> <p>h. No evidence of a suitable locking mechanism to hold the door open.</p> <p>i. Damaged or insecure tracking or detritus deposits within the tracking rails</p>
<p>Further information on disabled people's transport is available from the <b>Disabled Persons Transport Advisory Committee (DPTAC) website opposite</b> </p>	<p><a href="http://www.dptac.gov.uk">www.dptac.gov.uk</a></p>

## 11.2 FIRE EXTINGUISHER

Method of Inspection	Reason For Rejection
<p>a. Check the fire extinguisher for presence:</p> <ul style="list-style-type: none"><li>• the expiry date</li><li>• Seal.</li><li>• Type – water, CO<sub>2</sub> or foam or dry powder</li><li>• Approved mark - BS5423 or EN3</li></ul> <p>b. The fire extinguisher must be kept in an accessible position inside the vehicle. The extinguisher may be carried out of view, i.e. in a fastened glove compartment provided there is a clear sign on the dashboard, stating the location.</p>	<p>a. A fire extinguisher is missing or:</p> <ul style="list-style-type: none"><li>• out of date</li><li>• broken or missing seal.</li><li>• No approved marking visible or other non-approved marking shown</li></ul> <p>b. Not fitted in an accessible position or its position is not clearly marked.</p>



### 11.3 FIRST AID KIT

<b>Method of Inspection</b>	<b>Reason For Rejection</b>
<p>a. Check the first aid kit for presence, the expiry date and the seal is intact.</p> <p>b. The first aid kit must be kept in an accessible position inside the vehicle. The first aid kit may be carried out of view, i.e. in a fastened glove compartment provided there is a clear sign on the dashboard, stating the location.</p>	<p>a. A first aid kit is missing, out of date, broken or the seal has been broken.</p> <p>b. The first aid kit is not fitted in an accessible position or its position is not clearly marked.</p>

## **SECTION 12 – NOVELTY VEHICLES (STRETCH LIMOUSINES):**

### **Section Contents:**

<b>Sub-section</b>	<b>Subject</b>
12.1	Vehicle Identification Number (VIN)
12.2	Seating Capacity
12.3	Undue Stresses
12.4	Passenger Notices

## 12.1 Vehicle Identification Number (VIN)

Method of Inspection	Reason For Rejection
<p>Vehicle Identification Number (VIN), should be checked to ensure it complies with the guidance as follows:</p> <ul style="list-style-type: none"><li>• For vehicles constructed from 1998 onwards the VIN should begin with ILI;</li><li>• Pre 1998 vehicles (not recommended for licensing as private hire vehicles) VIN should begin with ILM;</li><li>• If a VIN begins with ILN or anything other, then this is likely to be a non approved ('cut-and-shut) modification.</li></ul>	<p>a. Inappropriate VIN markings displayed or no VIN markings present.</p>

## 12.2 Seating Capacity

<b>Method of Inspection</b>	<b>Reason For Rejection</b>
<p>It is strongly recommended that prior to the inspection of a novelty vehicle the inspector checks the seating capacity on the V5C to ensure it does not exceed 8 passenger seats.</p>	<p>If the V5C states more than 8 passengers, then this vehicle <b>MUST NOT</b> be tested or licensed as a Private Hire Vehicle. The vehicle should be referred to VOSA for licensing as a passenger carrying vehicle (PCV).</p>

### 12.3 Undue Stresses

Method of Inspection	Reason For Rejection
<p>Vehicle inspectors should be aware of undue stresses caused to the steering, brakes and tyres due to the additional weight imposed on the vehicle at the modification process.</p>	<p>Tolerances and wear should be as defined in the VOSA Car &amp; Light Commercial Vehicle Testing Manual as follows:</p> <ul style="list-style-type: none"><li>• Steering - Section 2</li><li>• Brakes - Section 3</li><li>• Tyres - Section 4</li></ul>

## 12.4 Passenger Notices

### Driver Declaration

Local licensing authorities are strongly advised to obtain a declaration, from the operator of a licensed novelty vehicle, that vehicles with side facing seats will never be used to carry passengers under 16 years of age, **regardless of whether the vehicle is fitted with or without seatbelts.**

### Passenger Notices

- i. In addition, notices forbidding children to be carried in side facing seats must be displayed in prominent positions, i.e. on entry to the passenger compartment and on the inside of the vehicle on either side of the passenger compartment. In addition, local licensing authorities may require outward facing signs adjacent to all entrance/exit doors to the passenger compartment.
- ii. Further notices should be displayed inside the vehicle, where all passenger can clearly read the notice, advising passengers of the maximum carrying capacity of the vehicle and a warning to passengers that should the capacity be exceeded then the vehicle will not be insured.

**HACKNEY CARRIAGE & PRIVATE HIRE**

**TRAILER INSPECTION SHEET**

Plate Number of towing vehicle: .....

Registration number of towing vehicle: .....

Registered owner of vehicle: .....

Manufacturers plate showing chassis number: .....

Manufacturers plate showing maximum weight: .....

<b>Inspection area</b>	<b>Description</b>	<b>Pass (✓)</b>	<b>Fail (x)</b>
Licence plate	Contains details & complies with local licensing authorities format		
Licence plate	Clearly displayed, legible, and securely fixed		
Licence plate	Serviceable – not damaged or defaced		
Trailer couplings	Check condition & operation and presence of a safety <i>breakaway</i> cable.		
Tow bar mounting brackets	Check condition and security		
Trailer body	Check condition of side and rear tailboards		
Trailer chassis	Check condition		
Suspension	Check condition and operation		
Wheel bearings	Check for excessive free play or roughness in bearings		
Tonneau cover & fittings	Check for condition		
Wheels and tyres	Check security, condition and wear		
Braking system	Operates satisfactorily		
Lighting	All obligatory lights work		
Indicators	All indicators work		
Reflective triangle	Check presence and condition		
Number plate	Check condition, security of fitting and displayed clearly		
Speed restriction notice	Check condition and displayed clearly		

I hereby certify that the above trailer has been inspected and has/has not\* been found to be roadworthy and suitable to be used as a hackney carriage/private hire\* trailer at the time of inspection.

Examined by (name) .....

Signature ..... Date.....

\* Delete as appropriate

## DEFINITION OF MOTOR VEHICLES

Appendix 'B'

Category	Definition
<b>M</b>	<b>A motor vehicle with at least four wheels designed and constructed for the carriage of passengers.</b>
<b>M<sub>1</sub></b>	Vehicles designed and constructed for the carriage of passengers and comprising no more than eight seats in addition to the drivers seat.
<b>M<sub>2</sub></b>	Vehicles designed and constructed for the carriage of passengers and comprising more than eight seats in addition to the drivers seat, and having a maximum mass not exceeding five tonnes
<b>M<sub>3</sub></b>	Vehicles designed and constructed for the carriage of passengers and comprising more than eight seats in addition to the drivers seat, and having a maximum mass exceeding five tonnes



## Hackney Carriage and Private Hire Vehicle Test Criteria

Hackney Carriage and Private Hire Vehicles in order to pass on the Part One and Part Two tests must ensure that:

### General Condition

- (a) Engine bay clean;
- (b) Vehicle exterior to be clean;
- (c) Interior lights required and to be working;
- (d) No rips in the upholstery or cigarette burns of more than two inches or multiple cigarette burns;
- (e) No rips in the carpet or floor covering;
- (f) Boot or luggage area must be dry and clean;
- (g) Front and rear demister in working order;
- (h) Where a vehicle is supplied with ashtrays they must be in place, unless the space where the ashtray was is blocked off to the satisfaction of the vehicle examiner;
- (i) li) There are no dents of more than two inches across;
- (j) No more than four dents per panel and not more than eight in total;
- (k) Scratches not more than two inches - pass (subject to below);
- (l) Any dents/scratches/stone chippings must not be rusting;
- (m) The colour of the vehicle must be consistent throughout;
- (n) If anything other than one colour any deviations should be done professionally;
- (o) Internal Private Hire and Hackney Carriage Vehicle Sticker must be placed in top left corner of front windscreen. Where the vehicle has a safety screen the sticker should be placed on this;
- (p) The external plate issued by the Council shall state the Private Hire Vehicle licence number, the maximum number of passengers which the Council has licensed the vehicle to carry and must be fixed on the rear of the vehicle. Where practicable the plate must be visible when the boot is in an upright position, and preferably low down on the extreme right or left hand side of the vehicle. The plate must not extend below the bumper line of the vehicle and not be placed in the rear window of the vehicle.

### Tyres

All tyres to be of same size.

### Car Numbers

A small call sign number on rear of vehicle.

### Scanning Equipment

The vehicle licence holder shall ensure that the vehicle is not equipped with any scanning equipment.

### Fire Extinguisher

Each licensed vehicle must carry a fire extinguisher of any type, it must be a minimum of one litre capacity. The Fire extinguisher shall be marked with the vehicle registration number in black permanent marker pen. A notice explaining where extinguisher located. The extinguisher must be securely fixed in a readily accessible position inside the vehicle or in the boot. Without the fire extinguisher the licence will not be issued.

### **First Aid Kit**

The first aid kit shall consist of the following:

- Eye pad;
- Triangle bandage ;
- Cleansing wipe;
- Powder free gloves;
- Conforming bandage;
- Washproof plaster.

### **For Wheelchair Accessible Vehicles**

- (a) The following will fail the Part Two Test:
- (b) Wheelchair securing straps not available;
- (c) Securing straps not adequately secured when not in use;
- (d) Seat belts not available for wheelchair passengers;
- (e) Securing straps have no means of release;
- (f) Securing mechanisms in floor present a trip hazard;
- (g) Rough edges are present on any device used to secure wheelchair.

### **Ramps**

The following will fail the Part Two Test:

- (a) Ramps are not able to be adequately secured when not in use;
- (b) No means of securing ramps to vehicle when in use (pins, clamps) etc;
- (c) Incline of ramps more the 1:12 (to pavement for side loading vehicles, to road for rear loading vehicles);
- (d) Ramps are not marked with maximum load bearing capacity;
- (e) Ramps are not permanently marked with vehicle registration number;
- (f) Rough edges are present on any device to secure a wheelchair;
- (g) Non-slip surface or raised edges not present on ramps.

### **Private Hire Vehicles Only**

No roof signs on Private Hire Vehicle

A licensed vehicle may not be a London type taxi (TX1 and Metrocab) or of such a design an appearance as to lead any person to believe that the vehicle is a Hackney Carriage.

If the licensed vehicle is hatchback or estate or minibus it must be fitted with a boot cover or guard rail to separate the rear luggage area from the passengers to the approval of the Council.

**Hackney Carriage and Private Hire vehicles:**  
**Plate test for motorised vehicles 2013**

1. The whole exterior of the vehicle must be adequately maintained and clean, to allow for identification, visual amenity and the protection of other's property;
2. The interior of the vehicle must be safe for all classes of the public;
3. Passenger seats must be a minimum of 406mm in width. In addition, there must be a minimum of 229mm of clear knee space, measured from the front portion of the passenger seat to the surface in front;
4. Where adjustable windows are installed, they must be capable of use by passengers to ensure comfort and safety;
5. An appropriate number of interior lights must be fitted to ensure passenger comfort and safety;
6. Any upholstery must be undamaged and unblemished for comfort, safety and visual amenity;
7. Carpet or floor covering must be secure to promote the safety of passengers;
8. The boot or luggage area of the vehicle must be clean and dry to ensure the protection of customer property and for visual amenity;
9. The boot or luggage area of the vehicle must be adequately equipped to ensure the safe and secure transportation of luggage;
10. Front and rear window demisters must be in good working order to enable the driver to maintain a good level of vision and awareness of the road at all times;
11. The Council issued vehicle internal identification sticker must be displayed so that it is clearly visible to all passengers;
12. The Council issued vehicle licence plate must be fixed so that, where practicable, it is visible when the boot is in an upright position. The plate must also not extend below the bumper line and must not be placed in the rear window of the vehicle;
13. All tyres fitted must be appropriate for the type of vehicle;
14. The vehicle must carry a fire extinguisher that meets the BS EN3 standard and bears the British Standard kitemark. It must be fitted with a seal to verify that it has not been used, permanently marked with the vehicle registration number and securely fixed in a easily accessible position;
15. Where a vehicle is fitted with a meter:
  - (a) It must be fitted so as to be visible to all passengers and;
  - (b) A current Council tariff card must be displayed so that it is clearly visible to all passengers;
16. The vehicle must carry a first aid kit which is fixed in an easily accessible position and;
  - (a) Contains at least one of each of the following items:
    - Eye pad
    - Triangle bandage

- Cleansing wipe
- Powder free gloves
- Conforming bandage
- Washproof plaster

(b) Where applicable, the items listed above must not be beyond their expiry date.

17. Doors must be capable of being secured in an open position to ensure passenger safety;

**Wheelchair accesible vehicles**

18. The vehicle must be equipped with a system that enables and promotes the safe, secure and comfortable boarding, conveyance and alighting of wheelchair bound passengers in accordance with the Hackney Carriage and Private Hire National Inspection Standards.

**Overall judgment of inspector**

19. At the time of the vehicle being tested, it must, in the inspector's opinion, be vehicle capable of withstanding the demands of operating as a licensed vehicle for the period of a year and therefore fit to be licensed as a Hackney Carriage or Private Hire vehicle.

DRAFT

**Motorised vehicle plate test**

Registration number

Plate number

Date of plate test

Chassis/VIN no.

<b>1.</b>	Is the whole exterior of the vehicle adequately maintained and clean, to allow for identification, visual amenity and the protection of other's property?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>2.</b>	Is the interior of the vehicle safe for all classes of the public?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>3.</b>	Are all of the passenger seats at least 406mm in width. And is there at least 229mm of clear knee space, measured from the front portion of the passenger seat to the surface in front?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>4.</b>	Where adjustable windows are installed, are they capable of use by passengers, to ensure comfort and safety?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b> <input type="checkbox"/> <b>N/A</b>
<b>5.</b>	Are there an appropriate number of interior lights fitted to ensure passenger comfort and safety?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>6.</b>	Is any upholstery undamaged and unblemished to ensure comfort, safety and visual amenity?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>7.</b>	Is the carpet or floor covering secure, to promote the safety of passengers?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>8.</b>	Is the boot or luggage area of the vehicle clean and dry to ensure the protection of customer property and for visual amenity?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>9.</b>	Is the boot or luggage area of the vehicle adequately equipped to ensure the safe and secure transportation of luggage?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>10.</b>	Are the front and rear window demisters in good working order to enable the driver to maintain a good level of vision and awareness of the road at all times?	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>11.</b>	Is the Council issued vehicle internal identification sticker displayed so that it is clearly visible to all passengers? (Not applicable to new vehicles)	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>
<b>12.</b>	Is the Council issued vehicle licence plate fixed so that, where practicable, it is visible when the boot is in an upright position? (The plate must not extend below the bumper line and must not be placed in the rear window of the vehicle.)	<input type="checkbox"/> <b>Yes</b> <input type="checkbox"/> <b>No</b>

13.	Are all of the tyres fitted appropriate for the type of vehicle?	<input type="checkbox"/> Yes <input type="checkbox"/> No
14.	Is the vehicle equipped with a fire extinguisher that (a) Meets the BS EN3 standard and bears the British Standard Kitemark? (b) Is fitted with a seal to verify that it has not been used? (c) Is permanently marked with the vehicle registration number? (d) Is securely fixed in an easily accessible position?	<input type="checkbox"/> Yes <input type="checkbox"/> No
15.	If the meter is fitted with a meter, is it: (a) Fitted to that it is visible to all passengers? (b) And is a Council tariff card displayed so that it is clearly visible to all passengers?	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
16.	Does the vehicle carry a first aid kit which is in an easily accessible position and is equipped with the following items which, where applicable, must not be beyond their expiry date: (a) Eye pad; (b) Triangle bandage; (c) Cleansing wipe; (d) Powder free gloves; (e) Conforming bandage; (f) Washproof plaster.	<input type="checkbox"/> Yes <input type="checkbox"/> No
17.	Are all doors capable of being secured in an open position to ensure passenger safety?	<input type="checkbox"/> Yes <input type="checkbox"/> No
18.	<b>For wheel chair accessible vehicles:</b> Is the vehicle equipped with a system that enables and promotes the safe, secure and comfortable boarding, conveyance and alighting of wheelchair bound passengers in accordance with the Hackney Carriage and Private Hire National Inspection Standards?	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
In the inspector's opinion, is the vehicle capable of withstanding the demands of operating as a licensed vehicle for the period or a year and thereby fit to be licensed as a Hackney Carriage or Private Hire vehicle?		<input type="checkbox"/> Yes <input type="checkbox"/> No – please write reasons for failure below.
Reasons for failure (use separate sheet if necessary):		

Inspector's signature

Inspector's name (printed)

Testing station name